

WHISPERFLO®



THE INDUSTRY STANDARD BY EVERY MEASURE ...

The correct pump should circulate all the water of a pool at least 4 times a day. Greater efficiency means lower running costs. The secret to greater efficiency is to minimize friction and turbulence. And less friction means also less noise.

WhisperFlo features an innovative hydraulic design that moves water more efficiently and more quietly than competitive pumps. Its engineered thermoplastic housing withstands extreme heat and resists corrosion. Engineered to provide optimum performance in any size pool or pool and spa combination, **WhisperFlo** is built to last a lifetime, and as a result, has become the industry's top seller for years.



- WhisperFlo costs less to operate, because it delivers higher performance with lower power consumption.
- Specially-engineered design assures whisper-quiet operation.
- Oversized strainer basket extends time between cleanings.
- See-through user-friendly Cam and Ramp™ lid makes inspection fast and easy - easy to remove and quickly locks in place with a quarter-turn.

WHISPERFLO®

See through lid

Oversized strainer basket

Thermoplastic housing



QUIET AND EFFICIENT

The **WhisperFlo** pump delivers maximum circulation efficiency at the lowest operating cost, and long, trouble free life with minimal maintenance. This legendary hydraulic design has been refined over 40 years for superior performance.

Additional features include:

- Advanced FunnelFlo™ diffuser and high-efficiency impeller maximize water flow and energy efficiency while minimizing turbulence and noise.
- Ideal for pool and spa combinations and for operating in-floor cleaning systems.
- Easy installation and trouble free servicing.
- Corrosion resistant, high-grade stainless steel motor shaft.
- Two-year limited warranty.

MODEL	kW	HP	VOLT	PHASE
P-WFL-071	0.55	¾	220-240V	1
P-WFL-073	0.55	¾	380-420V	3
P-WFL-101	0.75	1	220-240V	1
P-WFL-103E2*	0.75	1	380-420V	3
P-WFL-151	1.10	1.5	220-240V	1
P-WFL-153E2*	1.10	1.5	380-420V	3
P-WFL-201	1.50	2	220-240V	1
P-WFL-203E2*	1.50	2	380-420V	3
P-WFL-301	2.20	3	220-240V	1
P-WFL-303E2*	2.20	3	380-420V	3

* IE2-compliant



poolemea@pentair.com
www.pentairpooleurope.com

AVAILABLE FROM:

Copyright - Limited License: except as specifically permitted herein, no portion of the content on this document may be reproduced in any form or by any mean without the prior written permission of Pentair International SRL

[Automation](#) / [Filters](#) / [Filter Systems](#) / [Pumps](#) / [Cleaners](#) / [White Goods](#) / [Lighting](#) / [Sanitizers](#) / [Salt Chlorinators](#) / [Dosing and Measuring Equipment](#) / [Maintenance Accessories](#) / [Water Features](#)

NVA - BR - WFL - EN © 2012 Pentair International SRL. All Rights Reserved. Rev. 02-2013.

